

FS3201PA-F

Developed for Flight™ Technology

Advanced PA12-based Polymer Material perfect for high-performance functional Applications

Key Features:

- > Excellent mechanical properties
- > High toughness, durability and size-stability
- > High material re-usability

Example Applications:

- > Best fit for functional parts with requirements of high mechanical properties
- > Complex geometries with fine details
- > High-quality end-use parts fabrication


[Technical Data]

General Properties	Bulk Density	0.50 g/cm ³
	Part Density	1.04 g/cm ³
	Color	Black
Thermal Properties	Melting Point (10°C/min) <small>ISO 11357-1:2020</small>	185.5 °C
	Heat Deflection Temp(HDT) @1.8 MPa <small>ISO 78-1:2020</small>	62 °C
	Heat Deflection Temp(HDT) @0.45 MPa <small>ISO 78-1:2020</small>	147 °C
Mechanical Properties	Tensile Strength <small>ISO 527-1:2019</small>	44 MPa
	Tensile Modulus <small>ISO 527-1:2019</small>	1500 MPa
	Elongation at Break <small>ISO 527-1:2018</small>	35%
	Flexural Strength <small>ISO 178:2019</small>	49 MPa
	Flexural Modulus <small>ISO 178:2019</small>	1300 MPa
	Izod Impact Strength (notched) <small>ISO 180:2019</small>	6.0 KJ/m ²
	Izod Impact Strength (unnotched) <small>ISO 180:2019</small>	31 KJ/m ²

Disclaimer: Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon®, Buildstar®, Makestar® are registered trademarks of Farsoon Technologies. Last Change: 2022-01-29



High Frequency Muffler
System: Flight HT403P



Wire Frame
System: Flight HT403P

www.farsoon.com